

ATFO.9 Specification Parameters

LED Type	Mini 4in1
Pixel Pitch (mm)	0.9375
Pixel composition	1R1G1B
Physical Density (Dot/sqm)	1137778
Module resolution (W×H)	320×180
Module size (W×H) (mm)	300×168.75
Panel resolution (W×H)	640 x 360
Panel size (W×H×D) (mm)	600×337.5×48
Panel weight (kg)	7
Frame Made	Die-casting Aluminum
Brightness (cd/)	600
Color Temperature (K)	3200-9300
View Angle	140°/140°
Contrast Ratio	5000: 1
Drive Mode	1/46
Color Greyscale (bit)	16
Grey scale per color(level)	65536
Refresh rate(Hz)	3840
AC input Max Power (W)	500
AC input AVE Power (W/m2)	150
AC input voltage (V)	100-240
Frame Frequency (Hz)	50/60
Maintenance Mode	Front
Operating Humidity (RH)	10%-90%
Operating Temperature (°C)	-20— +60
IP Rating	IP40/IP40
Panel installation	Rigging/Stacking/wall mounting
Certificate	FCC+ Power supply UL



Copyright © 2020 by K-WAV. K-WAV is a registered trademark of K-WAV.
All rights reserved. KWAV-123456-0520

Connect With Us

Visit k-wav.com

Call 248-338-8084


Email info@k-wav.com



ATF1.2 Specification Parameters

ATF1.2-GOB specification parameters

LED Type	SMD 1010
Pixel Pitch (mm)	1.25
Pixel composition	1R1G1B
Physical Density (Dot/sqm)	640000
Module resolution (W×H)	240×135
Module size (W*H) (mm)	300×168.75
Panel resolution (W×H)	480 x 270
Panel size (W*H*D) (mm)	600×337.5×48
Panel weight (kg)	7
Frame Made	Die-casting Aluminum
Brightness (cd/M ²)	500
Color Temperature (K)	3200-9300
View Angle	160°/160°
Contrast Ratio	10000 : 1
Drive Mode	1/45
Color Greyscale (bit)	16
Grey scale per color(level)	65536
Refresh rate (Hz)	3840
AC input Max Power (W/m ²)	500
AC input AVE Power (W/m ²)	150
AC input voltage (V)	100-240
Frame Frequency (Hz)	50/60
Maintenance Mode	Front
Operating Humidity (RH)	10%-90%
Operating Temperature (°C)	-20— +60
IP Rating	IP40/IP40
Panel installation	Rigging/Stacking/wall mounting
Certificate	FCC+ Power supply UL



Copyright © 2020 by K-WAV. K-WAV is a registered trademark of K-WAV.
All rights reserved. KWAV-123456-0520

Connect With Us

Visit k-wav.com

Call 248-338-8084

Email info@k-wav.com



ATF1.5-GOB Specification Parameters

LED Type	SMD 1010
Pixel Pitch (mm)	1.56
Pixel composition	1R1G1B
Physical Density (Dot/sqm)	409600
Module resolution (W*H)	192×108
Module size (W*H) (mm)	300×168.7
Panel resolution (W*H)	384 x 216
Panel size (W*H*D) (mm)	600×337.5×48
Panel weight (kg)	7
Frame Made	Die-casting Aluminum
Brightness (cd/m ²)	500
Color Temperature (K)	3200-9300
View Angle	160°/160°
Contrast Ratio	10000 : 1
Drive Mode	1/48
Color Greyscale (bit)	16
Grey scale per color(level)	65536
Refresh rate (Hz)	3840
AC input Max Power (W/m ²)	500
AC input AVE Power (W/m ²)	150
AC input voltage (V)	100-240
Frame Frequency (Hz)	50/60
Maintenance Mode	Front
Operating Humidity (RH)	10%-90%
Operating Temperature (°C)	-20— +60
IP Rating	IP40/IP40
Panel installation	Rigging/Stacking/wall mounting
Certificate	FCC+ Power supply UL
Certificate	FCC+ Power supply UL



Copyright © 2020 by K-WAV. K-WAV is a registered trademark of K-WAV.
All rights reserved. KWAV-123456-0520

Connect With Us

Visit k-wav.com

Call 248-338-8084

Email info@k-wav.com



ATF1.8 Specification Parameters

LED Type	SMD 1010
Pixel Pitch (mm)	1.875
Pixel composition	1R1G1B
Physical Density (Dot/sqm)	284444
Module resolution (W×H)	160×90
Module size (W×H) (mm)	300×168.75
Panel resolution (W×H)	320 x 180
Panel size (W×H×D) (mm)	600×337.5×48
Panel weight (kg)	7
Frame Made	Die-casting Aluminum
Brightness (cd/m ²)	600
Color Temperature (K)	3200-9300
View Angle	140°/140°
Contrast Ratio	5000 : 1
Drive Mode	1/45
Color Greyscale (bit)	16
Grey scale per color(level)	65536
Refresh rate (Hz)	3840
AC input Max Power (W/m ²)	500
AC input AVE Power (W/m ²)	150
AC input voltage (V)	100-240
Frame Frequency (Hz)	50/60
Maintenance Mode	Front
Operating Humidity (RH)	10%-90%
Operating Temperature(°C)	-20— +60
IP Rating	IP40/IP40
Panel installation	Rigging/Stacking/wall mounting
Certificate	FCC+ Power supply UL
Certificate	FCC+ Power supply UL



Copyright © 2020 by K-WAV. K-WAV is a registered trademark of K-WAV.
All rights reserved. KWAV-123456-0520

Connect With Us

Visit k-wav.com

Call 248-338-8084

Email info@k-wav.com



ATF2.5 Specification Parameters

LED Type	SMD 1515
Pixel Pitch (mm)	2.5
Pixel composition	1R1G1B
Physical Density (Dot/sqm)	160000
Module resolution (W×H)	60×135
Module size (W×H) (mm)	150×337.5
Panel resolution (W×H)	240 x 135
Panel size (W×H×D) (mm)	600×337.5×48
Panel weight (kg)	7
Frame Made	Die-casting Aluminum
Brightness (cd/m ²)	600
Color Temperature (K)	3200-9300
View Angle(H/V)	140°/140°
Contrast Ratio	5000 : 1
Drive Mode	1/30
Color Greyscale (bit)	14/16
Grey scale per color(level)	65536
Refresh rate (Hz)	3840
AC input Max Power (W/m ²)	500
AC input AVE Power (W/m ²)	150
AC input voltage (V)	100-240
Frame Frequency (Hz)	50/60
Maintenance Mode	Front
Operating Humidity (RH)	10%-90%
Operating Temperature (°C)	-20— +60
IP Rating	IP40/IP40
Panel installation	Rigging/Stacking/wall mounting
Certificate	FCC+ Power supply UL
Certificate	FCC+ Power supply UL



Copyright © 2020 by K-WAV. K-WAV is a registered trademark of K-WAV.
All rights reserved. KWAV-123456-0520

Connect With Us

Visit k-wav.com

Call 248-338-8084

Email info@k-wav.com

