

TS3.9 Specification Parameters

LED Type	SMD 1921
Pixel Configuration	1R1G1B
Pixel Pitch(V/H) (mm)	V:3.91/ H:7.8
Physical Density (Dot/sqm)	32768
Module resolution (W*H)	128x16
Module size (W*H*D) (mm)	500x125x10
Panel resolution (W*H)	256x64
Panel size (W*H*D) (mm)	1000x500x94
Panel weight (kg)	4.5
Frame Made	Aluminum profiles
Brightness (nits)	800--5000
Color Temperature (K)	3200-9500
View Angle	160/160
Contrast Ratio	2000 ; 1
Drive Mode	Static
Color Greyscale (bit)	16
Grey scale per color(level)	65536
Refresh rate (Hz)	3840
AC input Max Power (W/m2)	800
AC input AVE Power (W/m2)	250
AC input voltage (V)	100-240
Frame Frequency (Hz)	50/60
Transparency rate	65%
Operating Humidity (RH)	10%-90%
Operating Temperature (°C)	-40— +45
IP Rating	IP20/IP20
Maintenance Mode	Rear
Panel installation	Rigging/Stacking



Copyright © 2020 by K-WAV. K-WAV is a registered trademark of K-WAV.
All rights reserved. KWAV-123456-0520

Connect With Us

Visit k-wav.com

Call 248-338-8084

Email info@k-wav.com

